



**4 Type**  
A Without bores

**Metric table**

Dimensions in: millimeters - inches

2			3			
l <sub>1</sub>			l <sub>2</sub>	d	h	s
60 2.36	120 4.72	160 6.30	30 1.18	6 0.24	12 0.47	5 0.20
60 2.36	120 4.72	160 6.30	40 1.57	6 0.24	12 0.47	5 0.20
60 2.36	120 4.72	160 6.30	50 1.97	6 0.24	12 0.47	5 0.20
60 2.36	120 4.72	-	60 2.36	6 0.24	12 0.47	5 0.20
160 6.30	-	-	60 2.36	8 0.31	15 0.59	6 0.24
160 6.30	200 7.87	-	80 3.15	8 0.31	15 0.59	6 0.24
160 6.30	200 7.87	-	100 3.94	8 0.31	16 0.63	7 0.28
220 8.66	-	-	100 3.94	13 0.51	26 1.02	10 0.39

**Specification**

- Body  
Steel profile **ST**  
Rolled, scaled or drawn  
Plain finish **BL**
- Pin  
Steel
- Load Rating Information → page 2088
- RoHS compliant

**On request**

- With loose pin
- With brass pin
- With lubricating nipple
- With bore holes
- Other dimensions
- Other finishes

**Information**

GN 1366 hinges are made of rolled or drawn steel profiles and are very robust.  
Type A can be assembled by welding or done via custom made holes in the hinge.  
Thanks to the standard dimensions, special applications and specific solutions can be realized even in relatively small quantities.  
**see also...**

- List of Hinge Types → page 1324
- Lift-Off Hinges GN 128 (Steel, Weldable) → page 1414
- Lift-Off Hinges GN 128.2 (Stainless Steel, Weldable) → page 1415
- Sheet Metal Hinges GN 136 (Steel or Stainless Steel) → page 1338 / 1339
- Sheet Metal Hinges GN 1362 (Stainless Steel, Weldable) → page 1340

<p>How to order</p> <p><b>GN 1366-ST-60-50-A-BL</b></p>	1	Material
	2	Width l <sub>1</sub>
	3	Length l <sub>2</sub>
	4	Type
	5	Finish