	⊥					
						_
ω			LAYOUT SHOWN	AS EXAMPLE		
Keying S	Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS35.7 MaxZ31 MaxVV THREADM25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum			Co		& Control List Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D51	7W06SDL		
-Temperature Range : -65°C to +175°C		A 17-10-2016				
-Salt Spray : 500 hours						
Mass : 29.9 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUS	TOMER DRAWING	N°
		TITLE	Alur	minium Plug 8D sei	ries	
		SCALE .	General line Tolerances		PRDS / PROJECT 859	
SHELL TYPE : Plug with RFI Shielding	Delivered W/O Cont				This document is the property of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17	ORIENTATION CONTACT TYPE : SOCKET(500 Matin	- SUURIAU	WWW.SOURIAU		SOURIAU it must not be reproduced or communicated without permission	
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 17		SOURI	AU DRG N°	SHEE	
		— A3		W06SDL-C	1/2	2

	I	۵	וד	m		0	
		Contact Layout					
4		$ \begin{array}{c} \bullet^{+Y} \\ \hline \\ E \\ \oplus \end{array} \begin{array}{c} A \\ \oplus \\ \hline \\ D \\ \oplus \end{array} \begin{array}{c} F \\ \oplus \end{array} \begin{array}{c} \Phi \\ \oplus \end{array} \end{array} \right) + x $					
	-X (Conta	Contacts (Insert arrangement 17-6)					
ω	size no. cor	(mm) (mm) +.121 (3.07) +.209 (5.31) +.241 (6.12) +.000 (0.00) +.000 (0.00) 241 (6.12) 241 (6.12) +.000 (0.00) 121 (3.07) +.209 (5.31)					
			-			SOURIAU shall not be liab due to a use of the Pro the Specifications issued by	oducts w y either o
0						(professional recor PN: 8D	Count FR
					A 17-10-20 ISS DATE Designed By:	116 First Release	
					TITLE SCALE NA	Genera Toler	Alumir ral linear rances: ±
					FORMAT	U WWW.SOUR SOU	
	Н	G	F	E	A3	8D5	17W
					V		

	B		А			
					4	
					3	
	non-conformit					
r of t		by a third party	Ý			
datio	on, technical n	otice.)				
ntry R	Juriso	liction & Contr Not Listed	ol List]	2	
·\						
VVV	06SDL					
		CUSTOMER	DRAWING	MOD N°		
CUSTOMER DRAWING						
ninium Plug 8D series						
ır		NPRDS /				
		85 This docu	Iment is the prop	perty of	1	
.CC	.COM SOURIAU it must not be reproduced or					
	DRG N°	communio	cated without pe	SHEET		
	6SDL-C			2/2		
	В		А	1	J	