


GL-2030M Aliases (UNFGL2030MXXXX) KEMET, GL, EMI/RFI Filters, Noise Suppression, 250 VAC



General Information Series GL Style Metal Box Description Noise Filters RoHS With Exemptions Qualifications UL, CSA, TUV 30 K Self-Temperature Rise Max. Miscellaneous Lead Screw Terminals **Terminal Type** Screw

Specifications		
Voltage AC	250 VAC	
Voltage	1500 VAC Withstanding Voltage 1 Min. Line to Ground	
Rated Current	3 A (AC/DC)	
Rated Temperature	55°C	
Temperature Range	-25/+55°C	
Leakage Current	0.5 mA MAX (250 V 60 Hz)	
Resistance	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground	

Click here for the 3D model.

Dimensions	
L	82mm NOM
W	56mm NOM
Н	38mm NOM
Lead	Screw Terminals

Packaging Specifications		
Packaging	Tray, Box	
Packaging Quantity	8	
Component Weight	200 g	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.