



NEMA 5-15  
SUPER-SAFEWAY  
PART NO. 1447  
COLOR: YELLOW

NEMA 5-15  
SUPER-SAFEWAY  
PART NO. 1547  
COLOR: YELLOW

#12-3 STJW, 300V CORD  
COLOR: YELLOW

**TECHNICAL:**  
 LISTED: cULus  
 RATED SUPPLY VOLTAGE: 120 VAC  
 RATED CURRENT: UP TO 15 AMPS OR CABLE RATING  
 RESET TYPE: AUTOMATIC OR MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 90 AMP 125 VAC  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	LENGTH "A"	POWER-UP
1301530043	15051-1A	2 FT 7 IN	1 FT ± 1 IN	AUTO
1301530052	15051-6A	7 FT 7 IN	6 FT ± 2 IN	AUTO
1301530046	15051-25A	26 FT 7 IN	25 FT ± 2 IN	AUTO
1301530049	15051-50A	51 FT 7 IN	50 FT ± 4 IN	AUTO
1301530044	15051-1M	2 FT 7 IN	1 FT ± 1 IN	MANUAL
1301530053	15051-6M	7 FT 7 IN	6 FT ± 2 IN	MANUAL
1301530047	15051-25M	26 FT 7 IN	25 FT ± 2 IN	MANUAL
1301530050	15051-50M	51 FT 7 IN	50 FT ± 4 IN	MANUAL

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FD = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: MIGRATION TO ECTR/NX	
	DIMENSION UNITS <b>INCH</b>	SCALE <b>NTS</b>	<p><b>molex</b></p> <p>120V 15A INLINE GFCI W/ 1447 &amp; 1547 NEMA 5-15</p> <p>PRODUCT CUSTOMER DRAWING</p> <p>DOCUMENT NUMBER: <b>SD-130153-015</b>    DOC TYPE: PSD    DOC PART: 001    REVISION: A1</p> <p>DRAWING: <b>D-SIZE</b>    SERIES: <b>130153</b>    MATERIAL NUMBER: SEE TABLE    CUSTOMER: GENERAL MARKET    SHEET NUMBER: 1 OF 1</p>	
GENERAL TOLERANCES (UNLESS SPECIFIED)				
ANGULAR TOL ± 0.5°				
4 PLACES ±	3 PLACES ±			
2 PLACES ± 0.13	1 PLACE ± 0.25			
0 PLACES ±	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			
THIRD ANGLE PROJECTION		EC NO: 684571 DRWN: VBASUTHKARP    2021/11/08 CHK'D: DNGUYEN62    2022/01/20 APPR: HKNEELAND    2022/02/02 INITIAL REVISION: DRWN: HRUIZ01    2013/02/06 APPR: JFMURPHY    2015/04/20		