


## A72UK1100AA00K

Aliases (72UK1100AA00K)

A72, Film, Film/Foil Polypropylene, General Purpose, 1000 pF, 10%, 500 VAC, 2000 VDC, 85°C

## **FRONT VIEW**



## **SIDE VIEW**



Click here for the 3D model.

Dimensions	,
D	8.5mm MAX
L	20.5mm MAX
LL	40mm +/-5mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	750

General Information		
Series	A72	
Dielectric	Film/Foil Polypropylene	
Style	Axial	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	
Component Weight	1.8 g	
Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C. maxK0 = 108000000.	

Specifications	
Capacitance	1000 pF
Capacitance Tolerance	10%
Voltage AC	500 VAC
Voltage DC	2000 VDC, 1500 VDC (105C)
Temperature Range	-55/+105°C
Rated Temperature	85°C
Dissipation Factor	0.05% 10kHz, 0.1% 100kHz
Insulation Resistance	100 GOhms
Max dV/dt	27000 V/us
Inductance	20.5 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.