

## Specification Sheet

Part Number: 596-00507



Foam Nameplate, Rectangular, 2.0" x 1.0", PET, Black, 500/roll

**Article Number**

596-00507

**Type**

NPL51X25BK

**Color**

Black (BK)

### Features & Benefits

- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
- Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
- Labels are UV and chemical resistant for long life in an industrial environment.
- Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Quantity Per**

roll

### Product Description

Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

<b>Short Description</b>	Foam Nameplate, Rectangular, 2.0" x 1.0", PET, Black, 500/roll
<b>Global Part Name</b>	NPL51X25BK-PET-BK
<b>Technical Description</b>	Foam Nameplate, 2.0" X 1.0" Rectangular Nameplate, PET, Black
<b>Width W (Imperial)</b>	2.0
<b>Width W (Metric)</b>	50.8
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	1.0
<b>Height H (Metric)</b>	25.4
<b>Width of Liner (Metric)</b>	55.88
<b>Width of Liner (imperial)</b>	2.2
<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Adhesive</b>	Acrylate with base of acrylic foam
<b>Halogen free</b>	Yes
<b>Adhesive Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)

**Operating Temperature (Metric)** -40°F to +176°F (-40°C to +80°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3919102055

**Content Unit(BMEcat)** pcs.

**Labels per Column** 1

**Labels per Row** 1

**Weight (Metric)** 0.22

**Weight (Imperial)** 0.5