

Front horizontal rail (A)



To accommodate guide rails and for the attachment of front panels.

- Front projection 2.5 mm corresponding to IEC 60 297-3
- HP pitch pattern of holes for the precise installation of guide rails
- M4 thread on end face
- Straight-through core hole
- Horizontal rail 192 HP without machining on the end faces. Suitable for cutting to length

Material:

Extruded aluminum section

Surface finish:

Clear-chromated or anodized

Usable width (HP)	Packs of	Order No.
4 (left)	1	3684.592
4 (right)	1	3684.955
8 (left)	1	3684.593
8 (right)	1	3684.956
12	1	3684.594
16	1	3684.595
20	1	3684.596
21	1	3685.985
40	1	3684.960
42	1	3684.560
63	1	3684.561
84	1	3684.562
84	2	3685.267¹⁾
192	1	3688.000²⁾

¹⁾ Including 4 assembly screws



²⁾ Anodised

! Also required:

Assembly screws M4 x 12, packs of 100, order no. 3654.300, see page 164

+ Accessories:

Threaded inserts (packs of 1), see page 114



Front horizontal rail, with double screw fastening (A1)



To accommodate guide rails and for the attachment of front panels. The double screw fastening ensures a high level of stability even under extreme loads.

- Load test to DIN EN/IEC 61 587-1, requirement level SL1
- Shock and vibration tests undertaken as per IEC 61 373 (DIN EN 50 155), Category 1, Class B
- Front projection 2.5 mm corresponding to IEC 60 297-3-101
- HP pitch pattern of holes for the precise installation of guide rails
- M4 thread on end face
- Straight-through core hole

Usable width (HP)	Packs of	Order No.
84	1	9908.721

Material:

Extruded aluminum section

Surface finish:

Clear-chromated

! Also required:

Assembly screws M4 x 12, packs of 100, order no. 3654.300, see page 164

+ Accessories:

Threaded inserts, order no. 3684.610 (packs of 1), see page 114

