


## C052C472K1G5CA

Aliases (C052C472K1G5CA)

LDD Comm COG, Ceramic, 4700 pF, 10%, 100 VDC, COG, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	4.83mm +/-0.25mm
Н	4.83mm +/-0.25mm
Т	2.29mm +/-0.25mm
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.635mm +0.102/-0.051mm
G	1.143mm MAX

Packaging Specifications			
Packaging	Bulk, Bag		
Packaging Quantity	100		

General Information			
Series	LDD Comm COG		
Style	Radial		
Features	Commercial		
RoHS	No		
Prop 65	★ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	8c864fd1-202b-4ce7-85fd-56c9e19121ad		
Termination	Lead (SnPb)		
Failure Rate	N/A		
AEC-Q200	No		

Specifications	
Capacitance	4700 pF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Dissipation Factor	0.1% 1 kHz 25C
Insulation Resistance	213 MOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.