

Specification Sheet

Part Number: 596-00674



Solar Label, Reflective, SOLAR DISCONNECT, 6.5" x 1.0", V, Red, 10/pkg

Article Number	596-00674
Type	SOLARD10
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">•Made with UV-stable inks and materials for durability and weather resistance.•Reflective properties to meet applicable NEC code requirements for reflective identification.•Supplied with an aggressive adhesive to ensure long life.•Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	pack

Product Description

HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.

Short Description

Solar Label, Reflective, SOLAR DISCONNECT, 6.5" x 1.0", V, Red, 10/pkg

Global Part Name

SOLARD10-505/281-RD

Technical Description

Pre-Printed Reflective Solar Label, 6.5" X 1", SOLAR DISCONNECT, Red

Local Order Number 2

Cross Reference = 50 per roll: 596-00246; Spanish version 50 per roll: 596-00810

Width W (Imperial)

6.5

Width W (Metric)

165.1

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.40

Material

Type 505/281, UV Stable Reflective Vinyl with Clear Polyester Laminate

Material Shortcut 505/281

Adhesive Acrylic

Halogen free No

Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C)

Operating Temperature (Metric) -40°F to +174°F (-40°C to +79°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB NEC2014

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity(Imperial) 10

Package Quantity (Metric) 10

Customs Number 3919905060

Labels per Column 1

Labels per Row 1

Weight (Metric) 0.521

Weight (Imperial) 1.14

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)