



Contact Layout



| Contacts<br>(Insert arrangement 17-8) |             |             |
|---------------------------------------|-------------|-------------|
| Contact position ID                   | Location    |             |
|                                       | X-axis (mm) | Y-axis (mm) |
| A                                     | +000 (0.00) | +236 (5.99) |
| B                                     | +128 (3.25) | +086 (2.18) |
| C                                     | +230 (5.84) | -078 (1.98) |
| D                                     | +094 (2.39) | -216 (5.49) |
| E                                     | -094 (2.39) | -216 (5.49) |
| F                                     | -230 (5.84) | -078 (1.98) |
| G                                     | -128 (3.25) | +086 (2.18) |
| H                                     | +000 (0.00) | -052 (1.32) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 17         | -8              | 8                  | 16            | II             | All              | MS20053-8  |

Panel Cutout



Max. thickness panel for receptacle: Type 0: front mounting = 3.2 mm, rear mounting = 2.5 mm

| Dim | Nominal    |
|-----|------------|
| ØA  | 30.96 min  |
| ØAA | 25.81 min  |
| R1  | 26.97      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D017K08AA

|                |   |   |                               |
|----------------|---|---|-------------------------------|
| B              | 11-04-17                                    | Drawing Update  |                               |
| ISS            | DATE  | Latest modification - by  | MOD N°                        |
| Designed By:   |   | Date:   | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |   |                               |
| SCALE          |   | General linear Tolerances: ±--  | NPRDS / PROJECT<br><b>859</b> |
| NA             |   | This document is the property of SOURIAU it must not be reproduced or communicated without permission |                               |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |   |                               |
| FORMAT         | <b>SOURIAU DRG N° 8D017K08AA-C</b>          |   | SHEET<br>2/2                  |