



Click [here](#) for the 3D model.

Dimensions

| | |
|----|---------------|
| D | 51.6mm +/-1mm |
| L | 74.5mm +/-1mm |
| T | 4.9mm NOM |
| S | 22mm +/-0.5mm |
| F | 15mm +/-0.5mm |
| DT | 15mm NOM |
| G | 13mm NOM |
| LT | 82.4mm +/-1mm |
| Z | 13mm NOM |

Packaging Specifications

| | |
|--------------------|-----------|
| Sleeving | Yes |
| Packaging | Bulk, Bag |
| Packaging Quantity | 20 |

General Information

| | |
|------------------|---|
| Series | PEH169_105 |
| Dielectric | Aluminum Electrolytic |
| Description | Screw Terminal, Aluminum Electrolytic |
| RoHS | Yes |
| Mounting | Stud |
| AEC-Q200 | No |
| Halogen Free | Yes |
| Component Weight | 180 g |
| Notes | Dimensions D And L Include Sleeving. M5. MS = M12x16. |

Specifications

| | |
|-----------------------|---|
| Capacitance | 3,300 uF |
| Capacitance Tolerance | -10/+30% |
| Voltage DC | 100 VDC |
| Temperature Range | -40/+105°C |
| Rated Temperature | 105°C |
| Life | 8000 Hrs (Rated Voltage And Ripple Current At 105C) |
| Resistance | 30 mOhms (100Hz 20C), 23 mOhms (100kHz 20C) |
| Ripple Current | 6.4 Amps (100Hz 105C), 33.8 Amps (10kHz 50C), 23.8 Amps (10kHz 40C) |
| Leakage Current | 4990 uA (5min 20°C) |
| Inductance | 16 nH (ESL) |