


C911U101KWYDAA7317

Not for New Design

C900AS SFTY X1-760 Y1-500, Ceramic, 100 pF, 10%, 760 VAC (X1), 500 VAC (Y1), Y5P, Lead Spacing = 10mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

C900AS SFTY X1-760 Y1-500
Radial Disc
Yes
Tin
N/A
UL, ENEC, VDE, CSA, CAN
No
Yes

Specifications	
Capacitance	100 pF
Capacitance Tolerance	10%
Voltage AC	760 VAC (X1), 500 VAC (Y1)
Dielectric Withstanding Voltage	4000 VDC
Temperature Range	-40/+125°C
Temperature Coefficient	Y5P
Dissipation Factor	2.5%
Insulation Resistance	10 GOhms
Safety Class	X1/Y1

Click	here	for	the	3D	model
-------	------	-----	-----	----	-------

Dimensions		
D	8mm MAX	
Т	7mm MAX	
S	10mm +/-1mm	
LL	20mm +1.5/-1mm	
F	0.55mm +/-0.1mm	
G	3mm MAX	

Packaging Specifications	
Packaging	Ammo
Packaging Quantity	1000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.