## ATGBICS QDD-400G-FR4-S Cisco Compatible Transceiver QSFP-DD, 400GBase-FR4, PAM4 (1310nm, SMF, 2km LC, DOM)

**Brand :** ATGBICS **Product code:** QDD-400G-FR4-S-C

**Product name :** QDD-400G-FR4-S Cisco Compatible Transceiver QSFP-DD, 400GBase-FR4, PAM4 (1310nm, SMF, 2km LC, DOM)




QSFPDD-FR4-400G Cisco Compatible Transceiver QSFP-DD, 400GBase-FR4, PAM4 (1310nm, SMF, 2km LC, DOM)

ATGBICS QDD-400G-FR4-S Cisco Compatible Transceiver QSFP-DD, 400GBase-FR4, PAM4 (1310nm, SMF, 2km LC, DOM):

ATGBICS QSFPDD-FR4-400G 400GBase-FR4 QSFP DD supports a distance of up to 2km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets or exceeds specification of Cisco QSFPDD-FR4-400G= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 400000 Mbit/s  Interface type * QSFP-DD  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  SFP transceiver standard  Maximum transfer distance  Wavelength  Ethernet LAN  Ethernet interface type  Digital Diagnostics Monitoring (DDM)  Wavelength-division multiplexing (WDM)	400000 Mbit/s QSFP-DD	Certification	CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%	
Features		Depth Height	72.4 mm 18.4 mm
Product colour Housing material	Silver W Metal  Metal	Weight	42 g
Plug and Play  Hot-Plug support  Hot-swap		Packaging data	
		Number of products included Package type	1 pc(s) Box
Easy to install		Technical details	
, , , ,		Sustainability compliance Sustainability certificates Doesn't contain	RoHS Lead



5056468770820

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.