

## Specification Sheet

Part Number: 596-00796

Made with UV stable inks and materials for durability and weather resistance.

Supplied with aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers.



Peel-Off Paint Shield, UV Stable, 3.6" x .9", PET, Clear, 10/pkg

**Article Number**

596-00796

**Type**

PAINTSHIELD5

**Color**

Clear (CL)

**Quantity Per**

pack

**Product Description**

HellermannTyton offers Paint Shield laminates that can be applied over Metal Solar Placards as a barrier against unintentional painting or graffiti. Paint Shields can also be used to provide additional protection for hand-written markings using a paint pen. HellermannTyton offers several sizes of Paint Shields designed to match all sizes of Metal Solar Placards. If a Paint Shield (covering placard) has been painted over, simply remove the shield to reveal original marking. Replace shield as needed.

<b>Short Description</b>	Peel-Off Paint Shield, UV Stable, 3.6" x .9", PET, Clear, 10/pkg
<b>Global Part Name</b>	PAINTSHIELD5-240-CL
<b>Technical Description</b>	3.60" X .90" Peel-off paint shield, UV Stable Clear Polyester, for use with 596-00838, 596-00841, 596-00842, 596-00857, 596-00858, 596-00859, 596-00237, 596-00238, 596-00239
<b>Width W (Imperial)</b>	3.6
<b>Width W (Metric)</b>	91.44
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	0.90
<b>Height H (Metric)</b>	22.86
<b>Material</b>	Type 240, 2.0 Mil Polyester, Clear (240)
<b>Material Shortcut</b>	240
<b>Adhesive</b>	1.0 Mil Aggressive Removable
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	from +50°F (from +10°C)
<b>Operating Temperature</b>	-20°F to +302°F (-29°C to +150°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Warranty (US)** Yes

**Package Quantity (Imperial)** 10

**Package Quantity (Metric)** 10

**Customs Number** 3919905060

**Labels per Column** 1

**Labels per Row** 1