


# ROHS COMPLIANT

PIN OUT: 1T01

Male	Female	Color
PIN1	PIN1	Black
PIN2	PIN2	Brown
PIN3	PIN3	Red
PIN4	PIN4	Orange
PIN5	PIN5	Yellow
PIN6	PIN6	Green
PIN7	PIN7	Blue
PIN8	PIN8	Purple
PIN9	PIN9	Gray
PIN10	PIN10	White
PIN11	PIN11	Pink
PIN12	PIN12	Light green
PIN13	PIN13	Black/white
PIN14	PIN14	Brown/white
PIN15	PIN15	Red/white
PIN16	PIN16	Orange/white
PIN17	PIN17	Green/white
PIN18	PIN18	Blue/white
PIN19	PIN19	Purple/white
PIN20	PIN20	Red/black
PIN21	PIN21	Orange/black
PIN22	PIN22	Yellow/black
PIN23	PIN23	Green/black
PIN24	PIN24	Gray/black
PIN25	PIN25	Pink/black
SHIELD	SHIELD	Drain Wire



LENGTH & P/N Table

LENGTH	BN P/N	CUSTOMER P/N
2.5FT (<762±20mm)	TL2G25C26HF1CK10-2.5FT-G	CS-DSDMDB25MM-002.5
5FT (<1524±30mm)	TL2G25C26HF1CK10-5FT-G	CS-DSDMDB25MM-005
10FT (<3048±50mm)	TL2G25C26HF1CK10-10FT-G	CS-DSDMDB25MM-010
15FT (<4572±50mm)	TL2G25C26HF1CK10-15FT-G	CS-DSDMDB25MM-015
25FT (<7620±100mm)	TL2G25C26HF1CK10-25FT-G	CS-DSDMDB25MM-025
50FT (<15240±200mm)	TL2G25C26HF1CK10-50FT-G	CS-DSDMDB25MM-050
125FT (<38100±300mm)	TL2G25C26HF1CK10-125FT-G	CS-DSDMDB25MM-125

CUSTOMER: Amphenol  
Cable Color: Gray(BN:HF)

⑦	Metal Foil	Copper	28X110X0.08mm	ZFCUSAX03
⑥	Heat Shrink Tube	EVA	Ø1.5X30mm	ZR1.5X30BK
⑤	Heat Shrink Tube	EVA	Ø1.5X10mm	ZR10.0BK
④	SR	PVC	Gray(BN:HF) UL94V-0	PLHPXXIO2NXX PLPVCXXHF2N35
③	THUMBSCREW	PC/STEBL	# 4-40thread,Nickel Plated,Gray PC	ZTADSUB05
②	CABLE	PVC	UL2464 25C 26AWG DRAIN+ALAMY	TC25DD26XXXXCX496
①	CONNECTOR	Copper alloy	25PIN Male , Nickel Plated, Gold Flash	ZDS25MXXXXXX
APPD.	P/N.		TL2G25C26HF1CK10-XXX-G	
CHKD.	FILE		TLXX25C26XXXXCK10.DWG	
DR.	TITLE		Deluxe 25PIN D-Sub MM	

REV.	DESCRIPTION	DATE	ENG.	APPROVAL
A1	Add writing color	16/JAN/2012	ZHEN HUJING	
A	NEW RELEASE	03/JAN/2007	ZHEN HUJING	

**BEST NICE ELECTRONIC**  
Tel:(07)526910206 6910230 Fax:6907192

SCALE	UNIT	SIZE	REV.
/	MM	A4	A1