



Click [here](#) for the 3D model.

### Dimensions

D	20.2mm +/-0.5mm
L	35.7mm +/-1mm
LL	3.3mm +/-0.5mm
F	1mm +/-0.03mm

### Packaging Specifications

Packaging	Tray
-----------	------

### General Information

Series	PEH227
Dielectric	Aluminum Electrolytic
Style	Radial Crown
Description	Radial Crown Ultra High CV Aluminum Electrolytic
RoHS	Yes
Lead	Radial Crown
Qualifications	AEC-Q200
AEC-Q200	Yes
Halogen Free	Yes
Component Weight	20 g
Shelf Life	156 Weeks

### Specifications

Capacitance	4,200 uF
Capacitance Tolerance	-10/+30%
Voltage DC	40 VDC, 32 VDC (150C)
Temperature Range	-40/+150°C
Rated Temperature	125°C
Life	8400 Hrs (Rated Voltage At 125C), 2000 Hrs (Rated Voltage At 150C)
Resistance	27 mOhms (100Hz 20C), 14 mOhms (100kHz 20C), 8 mOhms (5-100kHz 150C)
Ripple Current	25.5 Amps (5kHz 125C, With Heat Sink), 16.1 Amps (5kHz 140C, With Heat Sink), 7.2 Amps (5kHz 150C, With Heat Sink), 9 Amps (5kHz 125C), 11.4 Amps (5kHz 125C Max)
Leakage Current	508 uA (5min 20°C)