

EFA(02)-240X30MT0800 Aliases (UFSEFA020DT080, EFA(02)240X30MT0800)

KEMET, EFA, Flex Suppressors, Noise Suppression

	w	т
L		

General Information					
Series	EFA				
Style	Sheet				
Description	Flex Suppressor Flame Retardant Type				
Features	Flame Retardant Type				
RoHS	Yes				
Qualifications	UL94 V-0, UL File No. E176124				
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free				

Specifications		
Temperature Range	-40/+105°C	
Permeability	60 u At 3MHz	
Effective Frequency	1 MHz to 3GHz	
Specific Gravity	3.1TYP	
Thermal Conductivity	1.27 typical	
Surface Resistivity	1 MOhm/sq. TYP	

Click here for the 3D model.

Dimensions	,
Sheet Size	240mmx30M
L	30000mm NOM
W	240mm NOM
Т	0.2mm NOM

Packaging	Specification
-----------	---------------

Tape Description	Without PET Tape (Txx00)
Tape Thickness	0.03mm
Component Weight	4573.44 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.