



NOTES:

1. Using Temperature Range:
-40°C~+105°C
2. Screw Torque Value:0.78N • m(MAX)
3. RoHS Compliance

4	NUT	STEEL	Zn Plated
3	SCREW	STEEL	M3/Zn Plated
2	CLAMP	STEEL	Zn Plated
1	HOUSING	PA66	UL94-V0 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

DWG.	ZM.S	DATE	18.05.08	UNITS	MM	SHEET/OF	1 / 1
CHK.	Siber.Ma	DATE	18.05.08	SCALE	2:1 (:)		
APP.	Clark.Deng	DATE	18.05.08	NAME	SS4		
DINKLE ENTERPRISE CO.,LTD				DWG NO.	SP-03-SS400000		

REV.	CONTENT	NAME	DATE