


Data sheet | Item number: 706-3140/300-200

System cable; for Schneider Modicon Quantum; 2 x 16 digital inputs or outputs for higher voltages; Length: 2 m; Conductor cross-section: 0.34 mm²



www.wago.com/706-3140/300-200



i Picture differs from the item.

Color coding acc. to DIN VDE 47100 Cable 1; Channel 0-7	Interface connector 1			
	WAGO 231 connector (JA)		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	IN/OUT 0	1	L0
Brown	2	IN/OUT 1	2	L1
Green	3	IN/OUT 2	3	L2
Yellow	4	IN/OUT 3	4	L3
Grey	5	IN/OUT 4	5	L4
Pink	6	IN/OUT 5	6	L5
Blue	7	IN/OUT 6	7	L6
Red	8	IN/OUT 7	8	L7
Black	9	+L	10+20	L
Violet	10	-N	9+19	nc

Color coding acc. to DIN VDE 47100 Cable 2; Channel 8-15	Interface connector 1			
	WAGO 231 connector (JB)		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	11	IN/OUT 8	11	L8
Brown	12	IN/OUT 9	12	L9
Green	13	IN/OUT 10	13	L10
Yellow	14	IN/OUT 11	14	L11
Grey	15	IN/OUT 12	15	L12
Pink	16	IN/OUT 13	16	L13
Blue	17	IN/OUT 14	17	L14
Red	18	IN/OUT 15	18	L15
Black	19	nc	nc	nc
Violet	20	nc	nc	nc

Color coding acc. to DIN VDE 47100 Cable 3; Channel 16-23	Interface connector 2			
	WAGO 231 connector (JA)		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	1	IN/OUT 0	21	L16
Brown	2	IN/OUT 1	22	L17
Green	3	IN/OUT 2	23	L18
Yellow	4	IN/OUT 3	24	L19
Grey	5	IN/OUT 4	25	L20
Pink	6	IN/OUT 5	26	L21
Blue	7	IN/OUT 6	27	L22
Red	8	IN/OUT 7	28	L23
Black	9	+L	30+40	L
Violet	10	-N	29+39	N

Color coding acc. to DIN VDE 47100 Cable 4; Channel 24-31	Interface connector 2			
	WAGO 231 connector (JB)		PLC connector	
	Pin number	Wiring	Pin number	Signal
White	11	IN/OUT 8	27	L24
Brown	12	IN/OUT 9	28	L25
Green	13	IN/OUT 10	29	L26
Yellow	14	IN/OUT 11	30	L27
Grey	15	IN/OUT 12	31	L28
Pink	16	IN/OUT 13	32	L29
Blue	17	IN/OUT 14	33	L30
Red	18	IN/OUT 15	34	L31
Black	19	nc	nc	nc
Violet	20	nc	nc	nc

Data
Notes

Note

If less than 3 channels are used simultaneously, the maximum current per conductor is 2 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L. If more than 3 channels are used simultaneously, the maximum current per conductor is 0.75 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L.

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Electrical data

Inputs/outputs	2 x 16 digital inputs or outputs; for higher voltages
Operating voltage	≤ AC/DC 250 V
Current per wire (max.)	0.75 A

Compatibility

Schneider

Schneider Modicon Quantum	140 DAI 340 00
	140 DAI 353 00
	140 DAI 440 00
	140 DAI 453 00
	140 DAI 540 00
	140 DAI 543 00
	140 DAI 553 00
	140 DAI 740 00
	140 DAI 753 00
	140 DAO 840 00
	140 DAO 840 10
	140 DRA 840 00

Connection data

Cable type	LIYY
Color code	per DIN VDE 47100

Connection 1

Connector	WAGO 231 Series
Pole number 1	10
Connection type 1	System
Wire cross-section	0.34 mm ²

Connection 2

Connector 2	WAGO 231 Series
Pole number 2	10
Connection type 2	System

Subject to changes. Please also observe the further product documentation!



Connection 3

Connector 3	WAGO 231 Series
Pole number 3	10
Connection type 3	System

Connection 4

Connector 4	WAGO 231 Series
Pole number 4	10
Connection type 4	System

Connection 5

Connector 5	Schneider 140XTS00200
Pole number 5	40
Connection type 5	System

Physical data

Cable length	2 m
--------------	-----

Material Data

Weight	1408 g
--------	--------

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR
GTIN	4055143980241
Customs tariff number	85444290900

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Environmental Product Compliance

RoHS Compliance Status

Compliant, No Exemption

Downloads

Documentation

System Description

WAGO System Wiring, Selection Guide

pdf
545.9 kB

[Download](#)

This guide will help you select the appropriate interface modules and system cables for the controller you are using.

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-3140/300-200

[URL](#)

[Download](#)

System cable; for Schneider Modicon Quantum; 2 x 16 digital inputs or outputs for higher voltages; Length: 2 m; Conductor cross-section: 0.34 mm²

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.