

Interface module - UM 45-MKDS/MDSTBW/ 8SI/SO262 - 2319443


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse module, with screw connection, COMBICON connectors with stand-off and encoding against incorrect connection, for mounting on NS 35/7,5 or NS 32



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 046356 364898
GTIN	4046356364898

Technical data

Dimensions

Width	48.5 mm
Height	45 mm
Depth	160 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Maximum altitude	max. 2000 m
Degree of protection	IP20
	≥ IP54 (Installation location)

General

Nominal voltage U_N	230 V AC
Max. perm. current (per branch)	2 A
Mounting position	any
Degree of protection	IP20
	≥ IP54 (Installation location)

Connection data

Interface module - UM 45-MKDS/MDSTBW/ 8SI/SO262 - 2319443

Technical data

Connection data

Connection name	PCB connection
Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Number of positions	8
Conductor cross section solid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	26 ... 14

Connection data 2

Connection name	COMBICON connection
Connection method	Screw connection
Conductor cross section solid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Standards and Regulations

Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	230 V
Rated surge voltage	4 kV (1.2/50 µs)
Insulation	Functional insulation
Degree of pollution	2
Overvoltage category	III

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>