



| | | | | |
|------|-----|------|----------------------|---------------|
| 11.6 | 7.5 | 14.3 | 5055960801 | 8 |
| 9.1 | 5.0 | 11.8 | 5055960601 | 6 |
| 6.6 | 2.5 | 9.3 | 5055960401 | 4 |
| C | B | A | 製品番号 MATERIAL NO. | 極数 CIRCUIT |

注記
NOTES

- 適合端子 :5055979*00,561348*00,561349*00,593708*00
APPLICABLE TERMINAL:5055979*00,561348*00,561349*00,593708*00
- 適合リテーナー :505594 シリーズ
APPLICABLE RETAINER:505594 SERIES
- 材料 MATERIAL
ハウジング:ポリアミド(PA66 UL94V-0 黒)
HOUSING :POLYAMIDE(PA66 UL94V-0 BLACK)
ピン:黄銅,ニッケル下地 1μm Min. 錫メッキ(半光沢)1μm Min.
PIN :BRASS,Sn(MATTE) 1 MICROMETER MINIMUM
OVER Ni PLATING 1 MICROMETER MINIMUM

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

| | | | | | | | | |
|---|------------|------------|----------------|--|-----------------|------------------------|--|--|
| EC NO: 117526 DRWN: HKOBAYASHI CHK'D: SAKIYAMA REV APPR: TKANEKO | 2017/06/08 | 2017/06/28 | 2017/06/29 | GENERAL TOLERANCES (UNLESS SPECIFIED) | DIMENSION UNITS | SCALE | MUO 2.5 WW DUAL ROW CONNECTOR HOUSING ASSEMBLY PRODUCT CUSTOMER DRAWING | |
| | | | | ANGULAR TOL ± 3.0 ° | MM | 5:1 | | |
| | | | | 4 PLACES ± 0.2 | DRWN BY | DATE | | |
| | | | | 3 PLACES ± 0.2 | HKOBAYASHI | 2017/06/08 | | |
| | | | 2 PLACES ± 0.2 | CHK'D BY | DATE | | | |
| | | | 1 PLACE ± 0.2 | SAKIYAMA | 2017/06/28 | | | |
| | | | 0 PLACES ± 0.2 | APPR BY | DATE | | | |
| | | | | TKANEKO | 2017/06/29 | | | |
| | | | | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | DRAWING SIZE | THIRD ANGLE PROJECTION | | |
| | | | | | A3 | | | |
| | | | | | | | SERIES | |
| | | | | | | | 505596 | |
| | | | | | | | MATERIAL NUMBER | |
| | | | | | | | SEE CHART | |
| | | | | | | | CUSTOMER | |
| | | | | | | | GENERAL MARKET | |
| | | | | | | | DOCUMENT NUMBER | |
| | | | | | | | 5055960000-SD | |
| | | | | | | | DOC TYPE | |
| | | | | | | | PSD | |
| | | | | | | | DOC PART | |
| | | | | | | | 000 | |
| | | | | | | | SHEET NUMBER | |
| | | | | | | | 1 OF 1 | |