<u>Contact Dimensions:</u>
525-P.C. Tail .018 Sq.(0.46 Sq.) - Tail LG=.150(3.81)
.100 (2.54) Contact Spacing x .200 (5.08) Row Spacing 1 $[2x \ \emptyset.156 \]3.96]$ CARD SLOT ACCEPTS .054" [1.37] TO .070"[1.78] THICK PCB 6.800 172.72 6.960 [176.78] -7.275 [184.79] .160[4.06] POINT OF CONTACT CARD SLOT 330 [8.38] .250[6.35] **SECTION A-A** 600 [15.24]

- INSULATOR MATERIAL: THERMOPLASTIC PBT BLACK, UL 94V-0 CONTACT MATERIAL; COPPER TIN ALLOY
- CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SE	RIES CARD EDGE CONNECTOR
PART NUM	BER: 345-134-525-878



-7.535[191.39]

ACAD REFERENCE NO	. 345-ENG-MASTER
DRAWN: R.STA.MONICA	DATE:MAY.16/2017
CHECKED:	DATE:
SCALE: 1:1	SHEET 1 OF 2
DRAWING NUMBER	ISSUE

345-ENG-MASTER



.107 [2.72] .082 [2.08] .157 [4] .232 [5.89] .125(3.18) to .210(5.33) .125(3.18) to .210(5.33) Outside Tails Outside Tails .045(1.14) to .060(1.52) .045(1.14) to .060(1.52) Between Tails Between Tails **Contact Code 555 Contact Code 556**







Contact Code 558

Contact Code 559

Contact Code 560

INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0

DAP MATERIAL AVAILABLE UPON REQUEST

CONTACT MATERIAL; COPPER ALLOY

CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS

YOUR CONNECTION TO QUALITY & SERVICE

	ACAD REFERENCE NO	. 345-ENG-MASTER
3	DRAWN: R.STA.MONICA	DATE:MAY.16/2017
	CHECKED:	DATE:
,	SCALE: 1:1	SHEET 2 OF 2
ED.	DRAWING NUMBER	ISSUE

345-ENG-MASTER