



Title of Change:	Update to FPCN22642Z - Datasheet modification to adjust Vin test conditions for Load Regulation, Output Current Limit and Short Circuit current for the NCV8177 product family.
Proposed Changed Material First Ship Date:	1 March 2020 <i>or earlier with customer approval.</i>
Current Material Last Order Date:	Not Applicable
Current Material Last Delivery Date:	Not Applicable The Current Material Last Delivery Date may be subject to change based on build and depletion of the current (unchanged) material inventory.
Product Category:	Active components – Integrated circuits
Contact information:	Contact your local ON Semiconductor Sales Office or < Milos.Dvorak@onsemi.com >
Samples:	Contact your local ON Semiconductor Sales Office to place sample order or < PCN.samples@onsemi.com > Sample requests are to be submitted no later than 45 days after publication of this change notification.
Sample Availability Date:	1 March 2019
PPAP Availability Date:	Not Applicable.
Additional Reliability Data:	Not Applicable.
Type of Notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 12 months prior to implementation of the change or earlier upon customer approval. ON Semiconductor will consider this proposed change and it's conditions acceptable, unless an inquiry is made in writing within 45 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com .
Change Category	Type of Change
Data Sheet	Change of datasheet parameters/electrical specification (min./max./typ. values) and/or AC/DC specification Specification of additional parameters
Description and Purpose:	
<p>FPCN22642Z previously announced the change of the product datasheet to correct VIN for mentioned tests (Load Regulation, Output Current Limit and Short Circuit Current) and to add a new Output Current Limit test for VIN=1.6V. The change affects parts with output voltage 1.2V and below.</p> <p>This Update Notification announces the following:</p> <ol style="list-style-type: none"> 1. Corrected typo error on value of "Output Current Limit" under the "Before datasheet change" column from Vin=1.6V to Vin=1.7V 2. Corrected typo error of description under the "QA" column from "Typ" to "Min" 3. Corrected typo error of description under the "QA" column from "Max" to Typ" 	



Before Change

	Before datasheet change	After datasheet change	
	Test Conditions	Test Conditions	QA
			QA
			Typ
			MAX
Load Regulation	1 mA ≤ IOUT ≤ 500 mA, VIN = VOUT-NOM + 0.5 V or VIN = 1.6V (whichever is higher)	1 mA ≤ IOUT ≤ 500 mA, VIN = VOUT-NOM + 0.5 V or VIN = 1.75 V (whichever is higher)	
Output Current Limit	VOUT = VOUT-NOM - 100 mV, VIN = VOUT-NOM + 0.5 V or VIN = 1.6V (whichever is higher)	VOUT = VOUT-NOM - 100 mV VIN = VOUT-NOM + 0.5 V or VIN = 1.75 V (whichever is higher)	
Output Current Limit (New test in the datasheet)		VOUT = VOUT-NOM - 100 mV VIN = VOUT-NOM + 0.5 V or VIN = 1.6 V (whichever is higher)	300 600
Short Circuit Current	VOUT = 0 V, VIN = VOUT-NOM + 0.5 V or VIN = 1.6V (whichever is higher)	VOUT = 0 V, VIN = VOUT-NOM + 0.5 V or VIN = 1.75 V (whichever is higher)	

After Change

	Before datasheet change	After datasheet change	
	Test Conditions	Test Conditions	QA
			QA
			Min
			Typ
Load Regulation	1 mA ≤ IOUT ≤ 500 mA, VIN = VOUT-NOM + 0.5 V or VIN = 1.6V (whichever is higher)	1 mA ≤ IOUT ≤ 500 mA, VIN = VOUT-NOM + 0.5 V or VIN = 1.75 V (whichever is higher)	
Output Current Limit	VOUT = VOUT-NOM - 100 mV, VIN = VOUT-NOM + 0.5 V or VIN = 1.7V (whichever is higher)	VOUT = VOUT-NOM - 100 mV VIN = VOUT-NOM + 0.5 V or VIN = 1.75 V (whichever is higher)	
Output Current Limit (New test in the datasheet)		VOUT = VOUT-NOM - 100 mV VIN = VOUT-NOM + 0.5 V or VIN = 1.6 V (whichever is higher)	300 600
Short Circuit Current	VOUT = 0 V, VIN = VOUT-NOM + 0.5 V or VIN = 1.6V (whichever is higher)	VOUT = 0 V, VIN = VOUT-NOM + 0.5 V or VIN = 1.75 V (whichever is higher)	

Reason / Motivation for Change:

Correction of type error

Anticipated impact on fit, form, function, reliability, product safety or manufacturability

No anticipated impacts.

Sites Affected:

ON Semiconductor Sites:
All Sites

External Foundry/Subcon Sites:
All Sites

Marking of Parts/ Traceability of Change:

There are no changes to product marking or package labeling. Product traceability and ship history will distinguish product before and after this notification.



Reliability Data Summary:

Not applicable.

Electrical Characteristic Summary:

Electrical characteristics (specifications) are changed as noted in the document description. This change is to specification forcing functions only, as defined in the datasheet.

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Current Part Number	Qualification Vehicle
NCV8177AMX075TCG	NA
NCV8177AMX120TCG	
NCV8177BMX075TCG	
NCV8177BMX120TCG	
NCV8177AMTW090TCG	
NCV8177AMTW110TCG	
NCV8177AMTW120TCG	

Appendix A: Changed Products

Product	Customer Part Number	New Part Number	Qualification Vehicle
NCV8177AMTW090TCG		NA	SCY99192
NCV8177AMTW110TCG		NA	SCY99192
NCV8177AMTW120TCG		NA	SCY99192
NCV8177AMX075TCG		NA	SCY99192
NCV8177AMX120TCG		NA	SCY99192
NCV8177BMX075TCG		NA	SCY99192
NCV8177BMX120TCG		NA	SCY99192