


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes

	From	To
Wire Sizes	2 AWG	4-3 AWG STR & 2 AWG SOLID
Wire Types	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Lengths	1.0 in.	1-5/16 in.
Panduit Color Code on Barrels	BROWN	GRAY
Panduit Die Index No. on Barrels	P33	P29
Alternate Industry Die Index No. () on Barrels	(10)	(8)



				PANDUIT CORP. TINLEY PARK, ILLINOIS	
				RSC2-4-Q Copper Reducing Splice With Inspection Holes	
03	3/04	KLFU	KLFU	Wire size TO was: 4 AWG	11644
REV	DATE	BY	CHK	DESCRIPTION	ECN
					SCALE N/A
					DRAWING NO / CAD FILE
					RSC2-4-CUST