



NOTES:

1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE: 75 OHMS
CONTACT RESISTANCE: LESS THAN 50 MILLIOHMS
2. MATERIAL:
PLUG BARREL: COPPER ALLOY, SILVER PLATED.
PLUG HANDLE: COPPER ALLOY, NICKEL PLATED
CONTACT: COPPER ALLOY, SILVER PLATED
INSULATORS: TEFLON
3. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					UNLESS OTHERWISE SPECIFIED			FINISH	
					1. ALL DIMENSIONS IN INCHES [mm]			MATERIAL	
					- TWO PLACE DECIMALS ± 0.02 [0.5]			SPEC No.	
					- THREE PLACE DECIMALS ± 0.005 [0.13]			SCALE	
					FIRST USED ON			2:1	
A	28195	08/29/19	PC	TJK	DATE DRAWN	BY	CHKD	APVD	Switchcraft®
REV	ECO NUMBER	DATE	BY	APVD	5/01/17	PNK	PNK	SRC	
REVISIONS					DO NOT SCALE DRAWING				
					NAME			PART No.	
					TERMINATING PLUG			VMMSTPUHD	
					UHD SINGLE MICRO, RoHS			REV	
								A	

