




VMTSC15-20-M4-70-Z/25PK

Ruland VMTSC15-20-M4-70-Z/25PK, Vibration Isolation Mount, 15mm OD, M4 Threaded Stud, M4 Tapped Hole, 10mm Stud Length, 4mm Tapped Hole Depth, 20mm Height, 70 Shore A Natural Rubber Jacket, Steel

25 pack



Description

Ruland VMTSC15-20-M4-70-Z/25PK is a 25 pack of vibration isolation mounts, each with one tapped hole and one threaded stud. An individual vibration isolation mount has 15mm outside diameter, M4 threaded stud, M4 tapped hole, 10mm stud length, 4mm tapped hole depth, and 20mm height. Vibration isolation mounts are used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. The threaded stud side of a vibration isolation mount can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped hole on the component it will be mounted to. The tapped hole side can be mounted to the system by threading it onto an existing stud on the component. The rubber jacket that is made from natural rubber which has good elasticity and is well suited for most industrial equipment. Vibration isolation mounts in this pack have 70 Shore A hardness for the greatest rigidity and load capacity. Bodies are made from zinc plated steel allowing for high strength suitability in most industrial applications. These vibration isolation mounts are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	0.59 in (15 mm)	Height (H1)	0.79 in (20 mm)
Thread (TH)	M4 x 0.7	Plate Thickness (PT)	0.06 in (1.4 mm)
Stud Length (LS)	0.39 in (10 mm)	Tapped Hole Depth (LT)	0.16 in (4 mm)
Spring Rate	536.75 lb/in (94 N/mm)	Shore Hardness	70A (+/- 5)
Max Deflection	0.20 in (5.0 mm)	Max Axial Load	105.66 lb (470 N)
Multipack Quantity	25	Geometry	Cylindrical
Rubber Material	Natural Rubber	Metal Material	Zinc Plated Steel
Metallic Body Finish	Zinc-Plated	Country of Origin	Hungary
Weight (lbs)	0.452000	UPC	634529359969
Tariff Code	4016.99.6000	UNSPC	31162804
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		