



(1)





NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

.XX ±0.13


.XXX ±0.05

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED



POWER/CO-AX CON (IF PRESENT)	TACT RATING:	10A (CURRENT)
SIGNAL CONTACT C SIGNAL CONTACT R		5A PER CONTACT 10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
			DRAWN: C.B	DATE: JAN. 01/20	19	
			CHECKED:	DATE:		
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-17W2640-1NB		ISSUE	
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-17W2	2640-1NB	1	

-55°C ~ 125°C

5000MΩ min.

1000V AC rms



COMPLIANT

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

