

ATGBICS CPAC-TR-10LR-SSM160-SFP+-C network transceiver module Fiber optic 10000 Mbit/s SFP+ 1310 nm

Brand : ATGBICS **Product code:** CPAC-TR-10LR-SSM160-SFP+-

С

ATGRICS ATTRONOSTICATED

ATGRICS OTHER HOLD AND ATTRICTORY

PC << hd>hdm | hdm | hdm

Product name: CPAC-TR-10LR-SSM160-SFP+-C

Checkpoint Compatible Transceiver SFP+ 10GBase-LR 1310nm SMF 10km DOM

ATGBICS CPAC-TR-10LR-SSM160-SFP+-C network transceiver module Fiber optic 10000 Mbit/s SFP+ 1310 nm:

ATGBICS CPAC-TR-10LR-SSM160-SFP+ 10GBase-LR supports a distance of up to 10km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Checkpoint CPAC-TR-10LR-SSM160-SFP+= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic Maximum data transfer rate * 10000 Mbit/s Interface type * SFP+ Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) Fiber optic LC LR 10000 m 1310 nm 4 Companies the fiber optic In Gigabit Ethernet In Gigabit Ethernet In Gigabit Ethernet In Gigabit Ethernet	10000 Mbit/s SFP+	Country of origin Brand compatibility	United Kingdom Checkpoint
		Power	
	X LC	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%	
Wavelength-division multiplexing (WDM)	×	Weight & dimensions	
Features Product colour Housing material Plug and Play	Silver Metal ✓	Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 19 g
Hot-Plug support		Packaging data	
Hot-swap Easy to install		Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.