



## 2.75W Compact Fixed Blade USB Power Adapter (China)



### Features

- Fixed Blade
- No-Load Power Draw <0.3mW
- No Y Cap
- Low Cost
- Low Profile
- Level VI Efficient

### Applications

- Smart Phones
- PDA
- Personal Electronics
- Digital Camera

### Safety Approvals

- CCC

### Mechanical Characteristics

- Length: 42mm (1.65in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)
- Weight: 80g (3oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple <sup>(1)</sup> P-P (Max)	Regulation		Case Color
		Min.	Max.		Line	Load	
PSM03C-050Q-3-R	5V	0A	0.55A	100mV	±5%		Black

Notes: (1) Measured after 10 minutes with by-pass capacitors 0.1uf // 10uf at output connector terminal and oscilloscope set at 20MHz.  
 (2) Minimum order quantity applies for this model

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:****AC Input Voltage Rating**

100 to 240VAC

**AC Input Voltage Range**

90 to 264VAC

**AC Input Current**

0.1A(RMS) max.

**Leakage Current**

&lt;20uA, 264VAC/63Hz

**OUTPUT:****Power**

2.75W Maximum

**Efficiency**

DOE Level VI

68.95% at 115VAC/230VAC

**No-Load Power Saving**

≤75mW at 115VAC/230VAC

**Over-voltage Protection**

&lt;8.5V

**Short-Circuit Protection**

Latch requires power cycle to restart

**ENVIRONMENTAL:****Temperature**

Operation 0 to +40°C

Non-operation -40 to +85°C

**Humidity**

Operation 10 to 90%

**Immunity**

ESD: EN61000-4-2. Level 4

Surge: EN61000-4-5. Level 4

Harmonic: EN61000-3-2

Flicker: EN61000-3-3

**Emissions**

Complies with FCC Class B

Complies with EN55032 Class B

**Dielectric Withstand (Hi-pot) Test**

Primary to Secondary: 3000VAC

**Insulation Resistance**

Primary to Secondary: &gt;7M ohm 500VDC

**DC Output Connector**

USB A

D+ and D- pins shorted together inside the charger

Dimension Diagram Unit: mm

