

## Coaxial Cable Connector 11\_TNC-75-4-30/133\_N

### Description

Straight cable plug

Interface standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 75 $\Omega$ |
| Interface frequency max. | 1 GHz       |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | crimped   |
| Outer contact  | crimped   |
| Weight         | 0.0153 kg |

#### Environmental Data

|  |                  |
|--|------------------|
| Operating temperature                                | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant        |

#### Material Data

| Piece Parts    | Material   | Surface Plating                   |
|----------------|------------|-----------------------------------|
| Centre contact | Brass      | Gold Plating (Nickel underplated) |
| Outer contact  | Brass      | SUCOPLATE (R) Plating             |
| Body           | Brass      | SUCOPLATE (R) Plating             |
| Insulator      | PFA / PTFE |                                   |
| Coupling nut   | Brass      | SUCOPLATE (R) Plating             |
| Crimp ferrule  | Copper     | SUCOPLATE (R) Plating             |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00007215   |
| Catalogue drawing    | DOU-00006482   |
| Assembly instruction | DOC-0000179061 |

### Ordering Information

|                |                       |
|----------------|-----------------------|
| Single package | 11_TNC-75-4-30/133_NE |
|----------------|-----------------------|

### Additional Information

|                 |         |
|-----------------|---------|
| Suitable cables | S_04233 |
|-----------------|---------|