



## NOTES: UNLESS OTHERWISE SPECIFIED

- 1. RECEPTACLE MATERIAL: SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER
- 2. BACKSHELL MATERIAL: SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.
- 3. SPECIFICATIONS:
  - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
  - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
  - 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
  - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
  - 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
  - 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
  - 4.2. WITH ONLY LARGE BUSHING IN PLACE.
  - 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
  - 6.1 CONTACT SIZE AND WIRE RANGE.
  - 6.2 RETAINING RING COLOR.
- 6.3 MATING PART(S).
- 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





	AHDM04-24-23SR-059		HD34-24-23SE-059			
	PART NUMBER			DESCRIPTION	ITEM	
QUANTITY MATERIALS LIST						
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC +0.30   L Fractions +1/64		SIGNATURES DATE		Amphonol		
		DRAWN: J. HEAD	16MAR202	Amphenol		
2 PL DEC ±0.15 3 PL DEC ±0.08	2 PL DEC ±0.15 Angles ±1°			Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036		
MATERIAL SPECIFICATIONS:		CUSTOMER:		DURAMATE AHDM RECEPT, SIZE 24, WD THD,		
PROCESS SPECIFICATIONS:		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPIERTY OF THE AIMPHOLO CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		B C- AHDM04-24-23SR-059	41	
NEXT ASSY:				SCALE: NONE SHEET 1 OF	1	

DWG NO: AHDM04-24-23SR-059

REV: A1 SH: