



**TECHNICAL**

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	240VAC
RATED CURRENT:	UP TO 20 AMPS
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	120 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	NEMA 3R

MATERIAL NO.	PART NO.	OUTPUT CORD LENGTH	VOLTAGE
1301530203	30-0905	9.00 IN. ± 0.5"	240VAC
1301530204	30-0906	5.0 FT. ± 1.0"	240VAC
1301530205	30-0907	24.0 FT. +2.0"/-0.0"	240VAC

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FD = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: UPDATED GFCI BODY.						
	DIMENSION UNITS	SCALE	<p style="text-align: center;"><b>molex</b></p> <p style="text-align: center;">IN-LINE GFCI 20A, 240V FLYING LEADS</p> <p style="text-align: center;">PRODUCT CUSTOMER DRAWING</p>						
	INCH	NTS							
	GENERAL TOLERANCES (UNLESS SPECIFIED)								
DIVISIONAL SYMBOLS	ANGULAR TOL	±	°	EC NO: 730358					
	4 PLACES	±		DRWN: PPURSUTANDEL	2022/10/19				
	3 PLACES	±		CHK'D: DNGUYENG2	2023/02/16				
	2 PLACES	±		APPR: HKNEELAND	2023/02/21				
	1 PLACE	±		INITIAL REVISION:					
	0 PLACES	±		DRWN: PPURSUTANDEL	2021/12/13				
				APPR: HKNEELAND	2022/01/20				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	DOC TYPE	DOC PART	REVISION
			C-SIZE	130153	SEE TABLE	GENERAL MARKET	PSD	000	B

DOCUMENT STATUS	P1	RELEASE DATE	2023/02/21	03:30:54
-----------------	----	--------------	------------	----------