




## LVO-MCL-12-F

Ruland LVO-MCL-12-F, 12mm One-Piece Shaft Collar with Clamping Lever, Steel Collar with Zinc Plated Lever, 28mm OD, 11mm Width





## Description

Ruland LVO-MCL-12-F is a one-piece quick clamping shaft collar with clamping lever with a 12mm bore, 28mm OD, and 11mm width. It is made from MCL-12-F and LF30-CL-M4:12-ZS. The clamp style design does not mar the shaft, is easy to remove, and is indefinitely adjustable. The threaded stud on the lever is used in place of standard collar hardware. When combined, the two parts create a shaft collar that requires no tools to install, remove, or reposition and is ideally suited for packaging, printing, and other applications where frequent setup changes and adjustments are needed. Once the lever is installed in the shaft collar, users simply turn the lever until they meet their desired torque. The adjustable lever can be reposition by the user without the loss of holding power by lifting the handle and twisting it 40° to lock it in a new position. This allows for use in space constrained environments where 360° rotation is not possible to fully seat the lever. MCL-12-F is made from 1215 lead-free steel with a black oxide finish. LF30-CL-M4:12-ZS has a zinc plated steel handle and stainless steel threaded stud. This material combination allows for a durable quick clamping and release component with relatively high holding power that is suitable for most industrial applications. The lever is orange for safety and ease of identification. MCL-12-F is manufactured by Ruland and LF30-CL-M4:12-ZS is manufactured by Otto Ganter. LVO-MCL-12-F is RoHS3 and REACH compliant.

## **Product Specifications**

Prop 65	r roudet opcomeations			
Width (W)13 mmWidth Tolerance+0.076 mm / -0.254 mmLever Length L130 mmLever Height H232 mmHub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque4.6 NmScrew Location (R)10.01 mmNumber of Screws1 eaCollar Part NumberMCL-12-ELever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65WARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Bore (B)	12 mm	Bore Tolerance	+0.050 mm / +0.012 mm
Lever Length L130 mmLever Height H232 mmHub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque4.6 NmScrew Location (R)10.01 mmNumber of Screws1 eaCollar Part NumberMCL-12-FLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65WARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Outer Diameter (OD)	28 mm	Center to Lever Top H1	32.2 mm
Hub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque4.6 NmScrew Location (R)10.01 mmNumber of Screws1 eaCollar Part NumberMCL-12-FLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Width (W)	13 mm	Width Tolerance	+0.076 mm / -0.254 mm
Recommended Shaft Tolerance +0.000 mm / -0.013 mm Thread TH M4   Hex Wrench Size 3.0 mm Seating Torque 4.6 Nm   Screw Location (R) 10.01 mm Number of Screws 1 ea   Collar Part Number MCL-12-F Lever Part Number LF30-CL-M4:12-ZS-O   Collar Material Steel Collar Finish Black Oxide   Handle Color Orange Handle Material Zinc   Handle Finish Powder Coated Insert and Screw Material 303 Stainless Steel   Manufacturer Ruland Manufacturing Country of Origin Shaft Collar - USA Lever - Germany   Weight (lbs) 0.147800 UPC 634529292884   Tariff Code 8483.60.8000 UNSPC 31162811   Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular appli   Prop 65 CWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Lever Length L1	30 mm	Lever Height H2	32 mm
Hex Wrench Size3.0 mmSeating Torque4.6 NmScrew Location (R)10.01 mmNumber of Screws1 eaCollar Part NumberMCL-12-FLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Hub Diameter DH	13 mm	Sleeve Length L2	12 mm
Screw Location (R)10.01 mmNumber of Screws1 eaCollar Part NumberMCL-12-FLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Recommended Shaft Tolerance	+0.000 mm / -0.013 mm	Thread TH	M4
Collar Part NumberMCL-12-FLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65 <b>AWARNING</b> This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Hex Wrench Size	3.0 mm	Seating Torque	4.6 Nm
Collar MaterialSteelCollar FinishBlack OxideHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65 <b>AWARNING</b> This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Screw Location (R)	10.01 mm	Number of Screws	1 ea
Handle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Collar Part Number	MCL-12-E	Lever Part Number	LF30-CL-M4:12-ZS-O
Handle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65MARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Collar Material	Steel	Collar Finish	Black Oxide
ManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Handle Color	Orange	Handle Material	Zinc
Lever - Germany   Weight (lbs) 0.147800 UPC 634529292884   Tariff Code 8483.60.8000 UNSPC 31162811   Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular appli   Prop 65 AwaRNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Handle Finish	Powder Coated	Insert and Screw Material	303 Stainless Steel
Weight (lbs)0.147800UPC634529292884Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65AwaRNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic)	Manufacturer	Ruland Manufacturing	Country of Origin	
Note 1Performance ratings are for guidance only. The user must determine suitability for a particular appliProp 65AWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic	Weight (Ibs)	0.147800	UPC	
Prop 65	Tariff Code	8483.60.8000	UNSPC	31162811
· · · · · · · · · · · · · · · · · · ·	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Ethylene Thiourea	Prop 65	AWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), and Ethylene Thiourea		