

Ratings

Voltage: 300 V
 Temperature: -25 ~ 80 °C
 Flammability: VW-1

Conductor

Conductor count: 7
 Gauge: 24 AWG 0.22 mm²
 Material: tinned copper strands
 Strand size: $\varnothing 0.16 \times 11$
 Resistance at 20 °C: 94.2 Ω /km max

Insulator

Material: PVC
 Color: white, black, red, yellow, blue, green, orange
 Diameter: $\varnothing 1.2 \pm 0.10$ mm
 Nominal thickness: 0.28 mm
 Resistance at 20 °C: 10 M Ω /km min



Outer jacket

Material: PVC
 Color: gray
 Diameter: $\varnothing 5.2 \pm 0.30$ mm
 Nominal thickness: 0.80 mm

Wire marking: E339579 UL AWM STYLE 2464 24 AWG 80°C
 300V VW-1 --- cUL AWM I/II A 80°C 300V FT1 TENSILITY

Tests

Insulation tensile strength: 2.11 kgf/mm²
 Jacket tensile strength: 1.05 kgf/mm²
 After aging at 113 ± 2 °C for 7 days:
 Minimum tensile strength 70 % original
 Minimum elongation 65 % original
 Heat shock: 121 ± 1 °C /1 hour, no observed degradation
 Deformation: 121 ± 1 °C /1 hour, ≤ 50 %
 Cold bend: -10 ± 2 °C /1 hour, no observed cracking



Revision:	Date:	Description:	Prepared:	Notes: RoHS and REACH compliant	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com	
A	10/13/2015	Initial release	Verified:			Function test: no open, no short circuit, no intermittent
A1	1/26/2016	Updated stranding	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Wire, 7C TS, 24 AWG, UL2464, 300V, 80C, 5.20 mm, VW-1, PVC, gray	Size: A	Part number: 30-00515
A2	8/16/2018	Increased operating temperature range			Scale: 10:1	

5

4

3

2

1