


## NOTES:

MATERIAL:<br/>HOUSING:<br/>SHELL:<br/>CONTACT:THERMOPLASTIC POLYESTER, UL94V-0<br/>STEEL, NICKEL PLATED<br/>COPPER ALLOY, GOLD FLASH PLATEDOPERATING TEMPERATURE:<br/>(IF PRESENT)<br/>SIGNAL CONTACT CURRENT RATING:<br/>SIGNAL CONTACT RESISTANCE:30A (CURRENT)<br/>30A (CURRENT)<br/>10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

.XX ±0.13

.XXX ±0.05



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
		DRAWN: C.B	DATE: JAN. 01/20	19
		CHECKED:	DATE:	
EDAG INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
		DRAWING NUMBER: 630-21W1250-3N2		ISSUE
		PART NUMBER: 630-21W	1250-3N2	1

5000MΩ min.

1000V AC rms

