
THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25


.XX ±0.13 .XXX ±0.05



ISSUE NUMBER	
ORIGINAL	

1






NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


DIELECTRIC

WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED



OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)
SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE:	G: 5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.



	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY							
COME				COMBINATION D-SUB			C.B	DATE:	JAN. 0 ⁻	1/201	9
				CHECKED:			DATE:				
	EDACINC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE	SCALE:	(IN C.A.D. 1:1)	SHEET	1	OF	2			
			DRAWING NUMBER: 629-5W5-240-3T6					ISSUE			
YOUR CONNECTION TO QUALITY	NNECTION TO QUALITY & SERVICE MANUFACTURE OR SALE OF APPAR WITHOUT WRITTEN PERMISSION.		PART NUN	/BER: 629-5W5-	240-3T6			1			

1000V AC rms

13.20

COMPLIANT

