
т	۵	п	m	0







LAYOUT SHOWN AS

Keying Shown as example

Connector dimension

Е

Nominal

А

ISS

Designed By:

SCALE

NA

FORMAT A3

D

DATE

TITLE

SOURIAU

Dim

CHARACTERISTICS

Н

ω


-Standard : Based on MIL-DTL-38999 Series III

_								
\frown		: Composite				Р	3.25±0.2	
						PP	4.93±0.2	
	-Shell Plating	: Nickel				R1	31.75	
	-Insulator	: Thermoplastic				R2	29.36	
	-Contacts	: Copper Alloy				S V'	39.7±0.3	
	-Seals & Grommet	: Silicon Elastomer					18.7+1.4/-0 2.1/4.35	
\sim	-Contact Plating	: Gold over copper Alloy 0.8µm minimum				Z'	32 Max	
	-Durability	: 500 Mating cycles				VV THREAD	M31x1-6g	
	-Delivered with Souria	u contacts and Accessories						
	-Temperature Range	65°C to +200°C						Г
	-Salt Spray	: 2000 hours						
_	-Mass	: 47.5 g ± 10%						-
		-						
								-
	BASIC SERIES:	8D 0 - 21 M	41	S	С			
<u>→</u>	SHELL TYPE : Square	Flange Receptacle						
	CONTACT TYPE : Sta	ndard Crimp Contact					ORIEN	TATION : C
	SHELL SIZE : 21					CONTAC	CT TYPE : SOCKET(50	0 Matings)
	PLATING : M =	Nickel		L			CONTACT LAYO	UT : 21-41
			1					<u> </u>

F

G

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend



С

	Ξ		Þ					
	R.			4				
YOUT SHOWN AS EXA	MPLE			3				
not be liable for any r of the Products whic issued by either of th onal recommendatio Country FR N: 8D021M	h does not co ne Parties or l n, technical n Jurisc	mply with by a third party	DI List	2				
n - by		CUSTOMER	MOD	<u>N°</u>				
Composite I	Composite Receptacle 8D series							
General linearNPRDS / PROJECTTolerances:859								
.SOURIAU.COM it must not be reproduced or communicated without permission								
SOURIAU DRG N°SHEET8D021M41SC-C1/2								
	B		A					

ſ	Ξ	۵	IL	п	D	0	
		Contact Layout				P	anel Cutout
4	<	31° 23 31° 23			EX.	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING	
					¥.	Ø	<u>ØT_</u>
ω	Shell Arrangement Numb size no. cont 21 -41 4:	acts contacts rating location				Dim ØA ØAA R1 ØT	
	F						
						SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	roducts whi
N							Country FR
						PN: 81	D021N
						016 First Release	
					ISS DAT Designed By:	E Latest modification - by Date:	
					TITLE	Cor	mposite
-					SCALE NA		eral linear erances: ±
					SOURIA	WWW.SOUI	RIAU.CO
					FORMAT A3		JRIAU 021M4
l	Н	G	F	E	D	C C	

