

SMT Power Inductors

Unshielded Drum Core - PA0390NL Series



- ⌚ **Height:** 6.35mm Max
- ⌚ **Footprint:** 13.21mm Typ x 9.91mm Max
- ⌚ **Current Rating:** up to 17A
- ⌚ **Inductance Range:** 0.12μH to 10μH
- ⌚ 260°C reflow peak temperature qualified


Electrical Specifications @ 25°C - Operating Temperature -40°C to +125°C

Part ⁴ Number	Inductance @ 0Adc (μH ±20%)	Irated ¹ (A)	DCR (MAX) (mΩ MAX)	Saturation ² Current Isat (A)	Heating Current ³ Ibc (A)	SRF (MHz TYP)
PF0638.121NL *	0.12	17	1.5	28	17	200
PF0638.331NL	0.33	16	2	20	16	200
PF0638.681NL *	0.68	12	5	13	12	150
PF0638.102NL	1.0	10	6	11	10	100
PF0638.152NL *	1.5	9	10	9	9	90
PF0638.222NL	2.2	7.4	11	7.8	7.4	80
PF0638.272NL *	2.7	6.6	12	7	6.6	65
PF0638.332NL *	3.3	5.9	14	6.4	5.9	60
PF0638.392NL	3.9	5.3	15	5.9	5.3	50
PF0638.472NL *	4.7	4.8	18	5.4	4.8	45
PF0638.682NL *	6.8	4.4	25	4.6	4.4	40
PF0638.103NL *	10	3.7	34	4	3.7	32


Mechanical

Schematic

PF0638.XXXNL



SUGGESTED PAD LAYOUT



TAPE & REEL LAYOUT

Weight1.3 grams

Tape & Reel600/reel


Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified, all tolerances are $\pm \frac{.004}{0,10}$

Notes from Tables:

1. The rated current listed is the lower of the saturation current @ 25°C or the heating current.
 2. The saturation current, I_{sat} , is the current at which the component inductance drops by 10% (maximum) at an ambient temperature of 25°C. This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effects) to the component.
 3. The heating current, I_{bc} , is the DC current required to raise the component temperature by approximately 40°C. The heating current is determined by mounting the component on a typical PCB and applying current for 30 minutes.
 4. Optional Tape & Reel packaging can be ordered by adding a "T" suffix to the part number (i.e. PF0638.103NL becomes PF0638.103NLT). Pulse complies to industry standard tape and reel specification EIA481.
- * Contact Pulse for availability

Typical Inductance vs Current Characteristics



For More Information

Pulse Worldwide Headquarters

15255 Innovation Drive Ste 100
San Diego, CA 92128
U.S.A.

Pulse Europe

Pulse Electronics GmbH
Am Rottland 12
58540 Meinerzhagen
Germany

Pulse China Headquarters

Pulse Electronics (ShenZhen) CO., LTD
D708, Shenzhen Academy of
Aerospace Technology,
The 10th Keji South Road,
Nanshan District, Shenzhen,
P.R. China 518057

Pulse North China

Room 2704/2705
Super Ocean Finance Ctr.
2067 Yan An Road West
Shanghai 200336
China

Pulse South Asia

3 Fraser Street 0428
DUO Tower
Singapore 189352

Pulse North Asia

1F., No.111 Xiyuan Road
Zhongli District
Taoyuan City 32057
Taiwan (R.O.C)

Tel: 858 674 8100
Fax: 858 674 8262

Tel: 49 2354 777 100
Fax: 49 2354 777 168

Tel: 86 755 33966678
Fax: 86 755 33966700

Tel: 86 21 62787060
Fax: 86 2162786973

Tel: 65 6287 8998
Fax: 65 6280 0080

Tel: 886 3 4356768
Fax: 886 3 4356820

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2019. Pulse Electronics, Inc. All rights reserved.