



<b>Product / Process Change Notification (PCN)</b>																	
<input checked="" type="checkbox"/> Major change <input type="checkbox"/> Minor change																	
<b>PCN #:</b> PCN_ConTBL8_20221014  <b>Affected Series:</b> WE-ConTBL8 ; 6918050103xx  <b>PCN Date:</b> July 15, 2022  <b>Effective Date:</b> October 14, 2022	<b>Change Category:</b> <input type="checkbox"/> Equipment / Location <input checked="" type="checkbox"/> General Data <input type="checkbox"/> Material <input type="checkbox"/> Process <input type="checkbox"/> Product Design <input type="checkbox"/> Shipping / Packaging <input type="checkbox"/> Supplier <input type="checkbox"/> Software																
<b>Contact:</b> Product Management  <b>Phone:</b> +49 (0) 7942 - 945 5001  <b>Fax:</b> +49 (0) 7942 - 945 5179  <b>E-Mail:</b> pcn.eican@we-online.com	<b>Data Sheet Change:</b> <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No  <b>Attachment:</b> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																
<b>Description and purpose of change:</b> As a datasheet information amendment, Würth Elektronik updated the wire range but the product does not change. All datasheets will be updated on the effective date 2022-10-14. This is a datasheet update only. There will be no change in form, fit, function, quality or reliability of the product.																	
<b>Detail of Change:</b> This is only a datasheet update																	
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="text-align: left; padding: 5px;"><b>Wire Properties</b></th> <th style="color: red; padding: 5px;"><b>Before Change</b></th> <th style="color: green; padding: 5px;"><b>After Change</b></th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">Solid Wire Section (Imperial)</td> <td style="padding: 5px;">26 to 20 (AWG)</td> <td style="padding: 5px;">24 to 20 (AWG)</td> </tr> <tr> <td style="padding: 5px;">Solid Wire Section (Metric)</td> <td style="padding: 5px;">0.129 to 0.518 (mm<sup>2</sup>)</td> <td style="padding: 5px;">0.2 to 0.5 (mm<sup>2</sup>)</td> </tr> <tr> <td style="padding: 5px;">Stranded Wire Gauge Tin Dipped (Imperial)</td> <td style="padding: 5px;">26 to 20 (AWG)</td> <td style="padding: 5px;">24 to 20 (AWG)</td> </tr> <tr> <td style="padding: 5px;">Stranded Wire Section Tin Dipped (Metric)</td> <td style="padding: 5px;">0.129 to 0.518 (mm<sup>2</sup>)</td> <td style="padding: 5px;">0.2 to 0.5 (mm<sup>2</sup>)</td> </tr> </tbody> </table>			<b>Wire Properties</b>	<b>Before Change</b>	<b>After Change</b>	Solid Wire Section (Imperial)	26 to 20 (AWG)	24 to 20 (AWG)	Solid Wire Section (Metric)	0.129 to 0.518 (mm <sup>2</sup> )	0.2 to 0.5 (mm <sup>2</sup> )	Stranded Wire Gauge Tin Dipped (Imperial)	26 to 20 (AWG)	24 to 20 (AWG)	Stranded Wire Section Tin Dipped (Metric)	0.129 to 0.518 (mm <sup>2</sup> )	0.2 to 0.5 (mm <sup>2</sup> )
<b>Wire Properties</b>	<b>Before Change</b>	<b>After Change</b>															
Solid Wire Section (Imperial)	26 to 20 (AWG)	24 to 20 (AWG)															
Solid Wire Section (Metric)	0.129 to 0.518 (mm <sup>2</sup> )	0.2 to 0.5 (mm <sup>2</sup> )															
Stranded Wire Gauge Tin Dipped (Imperial)	26 to 20 (AWG)	24 to 20 (AWG)															
Stranded Wire Section Tin Dipped (Metric)	0.129 to 0.518 (mm <sup>2</sup> )	0.2 to 0.5 (mm <sup>2</sup> )															



**Reliability / Qualification Summary:**

There will be no change of the product, therefore no additional reliability or qualification testing will be performed.