


TOLERANCE UNLESS OTHERWISE SPECIFIED				
.X	±0.25			
.XX	±0.13			
XXX	±0.05			

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER
ORIGINAL ①



NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 20A (CURRENT)

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: 10mΩ MAX.

INSULATOR RESISTANCE:  $5000M\Omega$  min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms



COMPLIANT	

3.20

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.





THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC.,AND
SHALL NOT BE REPRODUCED,OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 630 COMBO ASSEMBLY			
DRAWN: C.B	DATE: JAN. 01/2019		
CHECKED:	DATE:		
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2		
DRAWING NUMBER: 630-47W	1640-2N4 ISSUE		

630-47W1640-2N4

PART NUMBER:

TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

2W2





5W1

0000 3W3







11W1

⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙






13W3










17W5










21W4











COMBINATION D-SUB



THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC.,AND
SHALL NOT BE REPRODUCED,OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

	DRAWN: C.B		DATE:	JAN.	01/20	19
	CHECKED:		DATE:			
;	SCALE: N.T.S		SHEET	2	OF	2
)	DRAWING NUMBER:	630-47W	1640-2N	4		ISSUE
6	PART NUMBER:	630-47W	1640-2N	4		1

630 COMBO ASSEMBLY

SW REFERENCE NO .: