



NOTES:

- 1. ELECTRICAL SPECIFICATIONS:**
 IMPEDANCE: 75 Ω
 FREQUENCY RANGE: 0-3 GHz
 W/S VOLTAGE: 250 Vrms
 INSULATION RESISTANCE: 1 GΩ min.
 CONTACT RESISTANCE: 30 mΩ max. (Initial)
 INSERTION LOSS: -1.0 dB max.
 RETURN LOSS: per SMPTE 424 M
- 2. MECHANICAL SPECIFICATIONS:**
 OPERATING TEMPERATURE: -40°C to +85°C
 LIFE: 500 cycles min.
- 3. MATERIAL:**
 SHELLS, MOUNTING NUT: COPPER ALLOY, NICKEL PLATED
 CONTACT: COPPER ALLOY, GOLD PLATED
 INSULATORS: THERMOPLASTIC
- 4. DIMENSIONS SHOWN FOR REFERENCE ONLY**
- 5. THIS PRODUCT IS RoHS COMPLIANT**

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE		
							4:1		
DATE DRAWN		BY	CHKD	APVD					
5/17/10		PNK	PNK	SRC					
			5/17/10	5/17/10					
REV					NAME		PART No.		REV
ECO NUMBER					DIN 1.0/2.3 FEED-THRU		DINFT		A
DATE					CONNECTOR, RoHS				
BY									
APVD									
REVISIONS									
A									
26775									
06/09/11									
BL									
TJK									