



WIRING SCHEMATIC

VOLTAGE RATING:	300V
AMPERAGE RATING:	max. 4A
PROTECTION CLASS:	IP 68
OPERATING TEMPERATURE:	FLEXING -5°C TO +80 °C STATIC -30 °C TO +80 °C

1200800008	WW4A31A09M020	6.56' +3.50" -0 [2.0M +88.9 -0]
1200800007	WW4A31A09M010	3.28' +2.19" -0 [1.0M +55.6 -0]
1200800006	WW4A31A09M006	1.97' +1.75" -0 [0.6M +44.5 -0]
1200800005	WW4A31A09M003	0.98' +0.75" -0 [0.3M +19.1 -0]
MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH

ITEM	COMPONENT	MATERIAL	FINISH
7	LABEL	MYLAR	BLACK/YELLOW
6	O-RING	VITON	GREEN
5	ULTRA-LOCK	BRASS	NICKEL PLATED
4	CONTACT	COPPER ALLOY	Au OVER Ni
3	INSERT	PUR	BLACK
2	OVERMOLD	PVC	YELLOW
1	CABLE #22	PVC	YELLOW

ENTER DESCRIPTION EC NO: WEU2010-0333 DRW: APOHL_WEU 2010/02/10 CHK: REISSNER 2010/02/11 APPR: FPACHER 2010/02/25	QUALITY SYMBOLS
	▼ = 0 ◻ = 0
	REVISION
	1

GENERAL TOLERANCES (UNLESS SPECIFIED)
mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± 0.1 1 PLACE ± 0.3 ± --- ANGULAR ± ---°
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	SCALE	DESIGN UNITS
IN/MM		METRIC
DRAWN BY	DATE	TITLE
APOHL_WEU	2010/02/10	MIC INL. SPLITTER XM PVC 90 DEGREE
CHECKED BY	DATE	
REISSNER	2010/02/11	
APPROVED BY	DATE	
FPACHER	2010/02/24	
MATERIAL NO.	DOCUMENT NO.	
	SEE NOTES	

THIRD ANGLE PROJECTION
MOLEX INCORPORATED SD-120080-020 1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION