


UNLESS O	TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X	±0.25			
.XX	±0.13			
.XXX	±0.05			

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 30A (CURRENT)

(IF PRESENT)

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT


SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms





COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	DRAWN: C.B	DATE: JAN. 01/2019			
	CHECKED:	DATE:			
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2			
Ì	DD4444140 A1144DED				

DRAWING NUMBER: 630-2W2-240-3N1 ISSUE PART NUMBER: 630-2W2-240-3N1

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. TOLERANCE UNLESS OTHERWISE SPECIFIED

.XX ±0.25 .XXX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)

2W2

○ **(**) ○ ○

 \circ

5W1

0000 3W3

3WK3

0...0 o

(<u>....</u>)

11W1

⊙ ⊙ ⊙ ⊙ ⊙ ⊙ ⊙ o

9W4

000000

13W3

00.....00

21W1

17W2

2

0000000

17W5

00000000 8W8 25W3



000:::::000

21W4







COMBINATION D-SUB



THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC INC.,AND
SHALL NOT BE REPRODUCED,OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

DRAWN: C.B		DATE:	JAN.	01/20	19	
CHECKED:		DATE:				
SCALE: N.T.S		SHEET	2	OF	2	
DRAWING NUMBER:	630-2W2-	240-3N1	1		ISSU	Ē

630-2W2-240-3N1

630 COMBO ASSEMBLY

SW REFERENCE NO .:

PART NUMBER: